

The Hose Guys, Inc.



[HOME](#) | [FITTINGS](#) | [HYDRAULIC HOSE](#) | [OIL FIELD HOSE](#) | [POWER WASH HOSE](#) | [MONTHLY SPECIALS](#) | [CONTACT US](#)

Print This Page

INTRODUCING OIL FIELD 5000 PSI

"Flexible Pipe"

5000 PSI Work Over Hose

**2" Inside Diameter
Rugged 4-Spiral Hi-Tensile Wire
Extended API Male Threads
Special Elongated "Heavy" Hex
130' Lengths Available**

**Tube: Seamless Oil Resistant Rubber
Cover: Abrasion & Oil Resistant Synthetic Rubber**

I.D.: 2.00"

O.D.: 2.716"

Working Pressure: 5000 PSI

Average Burst: 14,500 PSI

Min. Bend Radius: 35"

Weight Per Foot: 3.40 lbs.

Temperature: - 40* F / +212* F

IMPORTANT:

2" EN856 - FLEXIBLE PIPE - 5000 WP hose is designed for use on work over and well servicing rigs. For standard hydraulic fluid applications, 2" FLEXIBLE PIPE hose has a maximum working pressure of 3625 p.s.i.

[HOME](#) | [FITTINGS](#) | [HYDRAULIC HOSE](#) | [OIL FIELD HOSE](#) | [POWER WASH HOSE](#) | [MONTHLY SPECIALS](#) | [CONTACT US](#)

The Hose Guys Inc.

1325 Calle Avanzado
San Clemente, CA. 92673
949-940-1700
800-760-HOSE (4673)
FAX: 949-940-1708

Copyright 2008 The Hose Guys Inc.

Powered by Glacier web services.com